

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 Assembly foam
- **Application of the substance / the mixture** Construction chemicals
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 TYTAN PROFESSIONAL
 Selena Bohemia s.r.o.
 Na Strži 65/1702, 140 00 Praha, Česká republika
 tel.: +420 416 532 004
 e-mail: infocz@sena.com
 www.tytan.cz
- **Further information obtainable from:** msds@sena.com
- **1.4 Emergency telephone number:** European emergency number: 112 (24h)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
-----------	-----------	--



GHS08 health hazard

Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2	H351	Suspected of causing cancer.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335	May cause respiratory irritation.
Lact.	H362	May cause harm to breast-fed children.
Aquatic Chronic 4	H413	May cause long lasting harmful effects to aquatic life.

- **Additional information:**

Classification of the preparation with attributed H413 phrase, taking into account the content C14-C17 chlorinated alkanes, was made on the basis of acute toxicology tests; FEICA Position Paper 17.03.2014.

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 1)

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomers and homologues
chlorinated paraffins, C14-17

· **Hazard statements**

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H362 May cause harm to breast-fed children.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H413 May cause long lasting harmful effects to aquatic life.

· **Precautionary statements**

P102 Keep out of reach of children.
P260 Do not breathe gas.
P263 Avoid contact during pregnancy/while nursing.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Do not pierce or burn, even after use.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Do not spray on an open flame or other ignition source.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.
EUH204 Contains isocyanates. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 2)

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

• **3.2 Chemical characterisation: Mixtures**

• **Description:** Mixture: consisting of the following components.

• **Dangerous components:**

CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	30.0 - 60.0%
CAS: 1244733-77-4 EC number: 911-815-4 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chlorisopropyl)-phosphate ⚠ Acute Tox. 4, H302	< 25.0%
CAS: 85535-85-9 EINECS: 287-477-0 Reg.nr.: 01-2119519269-33-xxxx	chlorinated paraffins, C14-17 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10); Lact., H362	< 20.0%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21-xxxx	propane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	< 15.0%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31-xxxx	butane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	< 15.0%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	< 15.0%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-0001	dimethyl ether ⚠ Flam. Gas 1, H220; Press. Gas C, H280	< 10.0%

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• **4.1 Description of first aid measures**

• **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

• **After skin contact:**

Remove uncured foam using a piece of cloth and an unaggressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

• **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

• **After swallowing:**

Do not induce vomiting; call for medical help immediately.
Rinse out mouth and then drink plenty of water.

• **4.2 Most important symptoms and effects, both acute and delayed**

Notes to physician: The product irritates the respiratory tract and may trigger sensitisation of the skin and respiratory tract. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Extended medical treatment may be required depending on the degree of exposure and the severity of the symptoms.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: **TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves**

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Carbon dioxide.
Fire-extinguishing powder.
Foam.
Water spray.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet.
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Keep away from ignition sources.
Wear protective clothing.
Ensure adequate ventilation.
- **6.2 Environmental precautions:** Do not allow to enter sewers / surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents, e.g. acetone, alcohol. Remove cured foam mechanically.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation / exhaustation at the workplace.
Open and handle receptacle with care.
Do not pierce or burn even after use. Use only as directed on the label.
Do not mix with any other chemical products.
- **Information about fire - and explosion protection:**
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
This product is subject to regulations governing the storage of highly flammable aerosol products.
Storage rooms should be equipped with heat and smoke detectors.
Electrical equipment should be explosion-proof.
- **Information about storage in one common storage facility:**
Do not store together with acids.
Do not store together with alkalis (caustic solutions).
Store away from reducing agents.
Store away from oxidising agents.
Store away from foodstuffs.
Store away from plastic, rubber, aluminum, light-metals.
- **Further information about storage conditions:**
Store receptacle in a well ventilated area.
Store in vertical position in closed original containers.
Store at temperature from +5°C to +30°C.
Protect from frost.
Store under lock and key and out of the reach of children.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

WEL	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
	Sen; as -NCO

CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate

WEL	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
	Sen; as -NCO

CAS: 106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

CAS: 115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm
	Long-term value: 766 mg/m ³ , 400 ppm

· **DNELs**

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

	DNEL	20 mg/kg/day (General population, consumers)
Dermal	DNEL	0.05 mg/kg/day (General population, consumers)
Inhalative	DNEL	0.05 mg/m ³ (General population, consumers)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 5)

		0.05 mg/m ³ (Workers)
CAS: 115-10-6 dimethyl ether		
Inhalative	DNEL	471 mg/m ³ (General population, consumers) 1894 mg/m ³ (Workers)
CAS: 85535-85-9 chlorinated paraffins, C14-17		
Oral	DNEL	0.115 mg/kg/day (General population, consumers)
Dermal	DNEL	5.75 mg/kg/day (General population, consumers) 11.5 mg/kg/day (Workers)
Inhalative	DNEL	0.4 mg/m ³ (General population, consumers) 1.6 mg/m ³ (Workers)
CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate		
Oral	DNEL	0.52 mg/kg/day (General population, consumers) 1.04 mg/kg/day (Workers)
Dermal	DNEL	4 mg/kg/day (General population, consumers) 2.08 mg/kg/day (Workers)
Inhalative	DNEL	11.2 mg/m ³ (General population, consumers) 5.82 mg/m ³ (Workers)
· PNECs		
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
(freshwater)		1 mg/l
(sea water)		0.1 mg/l
(soil)		1 mg/kg
CAS: 115-10-6 dimethyl ether		
(freshwater)		0.155 mg/l
(sea water)		0.016 mg/l
(freshwater sediments)		0.681 mg/kg
(sea water sediments)		0.069 mg/kg
(soil)		0.045 mg/kg
CAS: 85535-85-9 chlorinated paraffins, C14-17		
(freshwater)		1 mg/l
(sea water)		0.2 mg/l
(freshwater sediments)		13 mg/kg
(sea water sediments)		2.6 mg/kg
(soil)		20 mg/kg
CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate		
(freshwater sediments)		13.4 mg/kg
(sea water sediments)		1.34 mg/kg
(soil)		1.7 mg/kg

· 8.2 Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- Do not inhale gases / fumes / aerosols.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 6)

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· **Material of gloves**

Polyethylene gloves.

Recommended thickness of the material: ≥ 0.02 mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

≥ 10 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

EN 166

· **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Rapidly curing foam dispensed by gaseous propellant from an aerosol container

Colour:

Different according to colouring

· **Odour:**

Characteristic

· **Change in condition**

Melting point/freezing point:

Not determined

Initial boiling point and boiling range: Not applicable, as aerosol

· **Flash point:**

< 0 °C
(propellant)

· **Auto-ignition temperature:**

$> +350$ °C (propellant)

· **Explosive properties:**

Heating may cause an explosion.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 7)

- | | |
|--|---|
| · Explosion limits: | |
| Lower: | 1,5 Vol % |
| Upper: | 11,0 Vol % |
| · Vapour pressure: | >500 kPa (in the container)
< 1*10 ⁻⁵ mmHg w 25°C (MDI) |
| · Density at 20 °C: | ≤ 1,3 (PMDI) g/cm ³ |
| · Solubility in / Miscibility with water: | Insoluble
Reacts with water |
| · 9.2 Other information | No further relevant information available |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Strongly reacts with water and other substances containing an active hydrogen atom.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**

- **Acute toxicity**
Harmful if inhaled.

- **LD/LC50 values relevant for classification:**

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

Oral	LD50	>10000 mg/kg (rat) (OECD401)
Dermal	LD50	>9400 mg/kg (rabbit) (OECD402)

CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate

Oral	LD50	9200 mg/kg (rat)
Inhalative	LC50/4h	178 mg/l (rat)

CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate

Oral	LD50	1,017 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 8)

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Suspected of causing cancer.
- **Reproductive toxicity**
May cause harm to breast-fed children.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

• 12.1 Toxicity

• Aquatic toxicity:

CAS: 85535-85-9 chlorinated paraffins, C14-17

EC50 >1000mg/l/48h (daphnia) (20%MCCP's)

>1000mg/l/72h (algae) (20%MCCP's)

NOEC >1000 mg/l (algae) (20%MCCP's)

CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate

EC50 47 mg/l (algae)

- **12.2 Persistence and degradability** Not biodegradable.
- **12.3 Bioaccumulative potential** Does not accumulate in organisms.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

• Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• European waste catalogue

08 05 01* waste isocyanates

16 05 04* gases in pressure containers (including halons) containing hazardous substances

15 01 10* packaging containing residues of or contaminated by hazardous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.02.2018


Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 9)

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA 	<p>1950</p>
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR, IMDG, IATA 	<p>AEROSOLS</p>
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR 	
<ul style="list-style-type: none"> · Class · Label 	<p>2 5F Gases. 2.1</p>
<ul style="list-style-type: none"> · IMDG, IATA · Class · Label 	<p>2 5F Gases. 2.1</p>
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	<p>No.</p>
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: 	<p>Warning: Gases. - F-D,S-U</p>
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Remarks: 	<p>1L E0 2 Exemption from ADR provisions by LQ principal (rule 3.4) - Inner packaging, max. 1 liter in capacity; outer packaging – max. gross weight of 30kg. - Inner packaging, max. 1 liter in capacity, based on common ground and covered with shrink film – max. gross weight of 20kg. Tunnel restriction code: D.</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN1950 AEROSOLS, 2.1</p>

GB

(Contd. on page 11)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 10)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
1907/2006/CE Regulation, REACH
1272/2008/CE Regulation, CLP
2015/830/UE Regulation
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 56
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**
None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H362 May cause harm to breast-fed children.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

- **Recommended restriction of use**

The information stated above is based on current knowledge and applies to the product in the form in which it is used. Data concerning this product is presented in order to fulfill safety requirements and not to guarantee its specific properties.

In cases when application conditions are not subject to manufacturer's control, the responsibility for safe product use and obeying law regulations in particular, lies on the user's side.

Information in the appropriate technical data sheet of product.

- **Department issuing SDS:** Product safety department.

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2018

Version number 34

Revision: 03.06.2016

Trade name: TYTAN PROFESSIONAL Thin Bed Mortar GUN PU Foam Adhesive 750 ml grey CZ gloves

(Contd. of page 11)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas C: Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Lact.: Reproductive toxicity – effects on or via lactation
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

*** Data compared to the previous version altered.**

- 1) So far unclassified substance CAS: 13674-84-5 added in pt 3; MDI reclassification.
- 2) Change in classification of compound in pt 2.
- 3) Change in storage temperature in pt 7.
- 4) Pts 11 & 12 enhanced by data for new substances.
- 5) Information about collection of empty containers in 13 pt have been removed.
- 6) Change in pt 15 resulting from compound reclassification.
- 7) CLP classification.

Update date: 03.06.2016